



BIGFOOT 2

Portable Sound System



Perfect for...

- Indoor & Outdoor Events
- Football Field
- Schools & Universities
- Sporting Events
- Marching Bands
- Graduations
- Large Auditoriums
- Assemblies
- House of Worship
- Parks & Recreation
- Auctions
- Military Training & Ceremonies
- Fitness Centers
- Parades & Community Celebrations
- Ceremonies
- Public Gatherings
- Weddings
- and more!





TECH SPECS

- 130 dB of clear sound
- 300W AC/DC
- 1.9 GHz wireless frequency
- Two universal microphone input jacks
- 1/4" & 3.5 mm AUX line input
- 1/4" line output
- Built-in rechargeable Lithium Ion batteries
- Five 8" neodymium woofers
- One neodymium compression driver

FEATURES

- Reaches crowds of 5,000+
- Connect up to four wireless mics
- Anchor AIR compatible
- Built-in Class 1 Bluetooth
- Onboard mic storage bag
- Heavy duty wheels for easy transport
- Built-in rechargeable batteries operate 6 - 8 hours on a single charge
- Designed to cover a football field or large auditorium



(BIG2-XU4 Back Panel)

Bigfoot 2 Models

BIG2	Bigfoot with built-in Bluetooth
BIG2-U2	Bigfoot with built-in Bluetooth & dual wireless mic receiver
BIG2-U4	Bigfoot with built-in Bluetooth & two dual wireless mic receivers
BIG2-X	Bigfoot with built-in Bluetooth & AIR wireless transmitter
BIG2-XU2	Bigfoot with built-in Bluetooth, AIR wireless transmitter & dual wireless mic receiver
BIG2-XU4	Bigfoot with built-in Bluetooth, AIR wireless transmitter & two dual wireless mic receivers
BIG2-R	Bigfoot with built-in Bluetooth & AIR wireless receiver
BIG2-RU2	Bigfoot with built-in Bluetooth, AIR wireless receiver & dual wireless mic receiver
BIG2-RU4	Bigfoot with built-in Bluetooth, AIR wireless receiver & two dual wireless mic receivers

Microphones

WH-LINK	Wireless handheld mic (1.9 GHz)
WB-LINK	Wireless belt pack transmitter (1.9 GHz)
HBM-LINK	Headband mic (3.5 mm plug)
CM-LINK	Collar mic (3.5 mm plug)
EM-LINK	UltraLite mic (3.5 mm plug)
LM-LINK	Lapel mic (3.5 mm plug)
MIC-90	Wired wandheld mic with 20 ft. cable (XLR plug)

Technical Specifications

Rated Power Output	300 watts AC/DC
Max SPL @ Rated Power	130 dB @ 1 meter
Frequency Response	100 Hz – 15 kHz ± 3 dB
Microphone Wireless Frequency	1.9 GHz DECT
Microphone Wireless Range	300'+ line of sight
Mic Inputs	Lo-Z, balanced, XLR & 1/4" 34V DC condenser mic (phantom) power Hi-Z (10 KΩ), unbalanced, 1/4" phone
Line Inputs	Unbalanced 1/4" & 3.5 mm stereo
Line Output (post fader)	Isolated, 600Ω, 1/4" phone
AC Power Reqs.	100 – 240 VAC, 50/60 Hz, 300W max
Battery	Three 12V LFP rechargeable batteries, 7.5 AH
Dimensions Closed (HWD)	42.5" x 14" x 23" (108 x 38.9 x 61 cm)
Dimensions Opened (HWD)	68.5" x 14" x 23" (174 x 38.9 x 61 cm)
Weight	63.5 lbs / 28.8 Kg
Warranty	6 years

Sensitivity For Rated Output

Lo-Z Microphone	-52 dBV (2.5 mVrms)
Hi-Z Microphone	-43 dBV (7.5 mVrms)
Auxiliary (line)	-14 dBV (200 mVrms)

Anchor AIR Technical Specifications

AIR Frequency Range	902 - 928 MHz
AIR Wireless Range	300'+ line of sight



(Features & Specifications Subject to Change Without Notice)